

OV Sensor matched with Largan Lens

1. Largan offers products with model # below.
2. Price may be negotiable depends on model and quantity.
3. Start quote at least 100 units

For mobile phone:

Type	Sensor	Lens	Structure	Fno.	*TTL	CRA	FOV	Image Circle	Status	PS	
1.0M	OV9282(B&W) 3u, 1/4" CRA ≈ 27°										
2.0M	OV2281(B&W) 1.12u, 1/7.3" CRA ≈ 30°	40144	4P	2.2	4.535	21.6	27.8	2.89	0k		
4.0M	OV4688 2.0u, 1/2.9" CRA ≈ 31°	9598	5P	2.00	4.81	33.3	77.5	6.60	ok	接單生產	
		50091	5P	2.00	4.13	34.1	81.6	6.50	ok	接單生產	
		60005	6P	2.20	4.5	34.6	78.3	6.6	ok	接單生產	
5.0M	OV5693/5695 1.4u, 1/4" CRA ≈ 30°	30021	3P	2.80	4 - 4.15	27.0	66	4.80	ok	COB type	
		40039	4P	2.20	4.20	26.7	65.8	4.90	ok	COB type	
		40075B2/B5	4P	2.40	3.85	28.4	73.8	4.80	ok	COB type	
		40093	4P	2.20	3.45	32.6	84	4.80	ok	COB type	
		50019	5P	2.00	3.70	33.0	80	4.84	ok	COB type	
		40103	4P	2.40	3.40	31.9	88	4.80	ok		
		40114	4P	2.40	3.40	32.5	74.9	4.80	ok	From 40100	
		40118	4P	2.20	3.45	32.7	75.4	4.80	ok		
		40135	4P	2.40	3.70	32.8	80	4.84	ok		
		40137	4P	2.20	4.10	31.7	84.1	4.80	ok		
		40138	4P	2.20	2.73	32.5	80.4	3.73	ok		
	40147	4P	2.00	3.34	33.3	83.3	4.90	ok	From 40145		
	OV5675 1.1u, 1/5" CRA ≈ 31°	40117	4P	2.00	3.30	31.9	75.0	3.90	ok		
		30048	3P	2.20	2.80	33.9	75	3.93	ok		
		30051	3P	2.20	3.10	32.0	80.0	3.88	ok		
		30055	3P	2.20	2.83	33.7	84.8	3.90	ok		
		40106	4P	2.20	3.25	29.4	69.0	3.88	ok		
		30057	3P	2.20	3.35	33.0	73.5	3.93	ok		
		40120	4P	2.20	3.00	32.1	85.0	3.78	ok		
	8.0M	OV8865 1.4u, 1/3.2" CRA ≈ 33°	9574	5P	2.00	4.60	32.0	77.2	6.10	ok	COB type
			50008	5P	2.20	4.45	32.4	72.9	6.17	ok	同 50013
50042			5P	2.20	4.25	34.0	79.6	6.01	ok		
50045			5P	2.40	4.25	33.0	80.0	6.01	ok		
50075			5P	2.20	4.60	34.9	86.0	6.20	ok	From 50039B	
50060			5P	2.00	4.50	32.0	73.5	6.17	ok		
50063			5P	2.20	4.23	32.0	77.0	6.07	ok		
50066			5P	2.00	4.20	34.5	76.4	6.17	ok	From 50065B	
50087			4P	2.20	3.94	35.0	78.3	6.17	ok	From 50064B	
50093			5P	2.20	4.30	32.6	75.1	6.20	ok	From 50069B	
50115			5P	2.00	4.10	32.9	78.0	6.05	ok		
50119		5P	2.00	4.30	33.1	76.1	6.19	ok	From 50113		
50135		5P	1.90	4.30	32.0	80.0	6.01	ok			
OV8856 1.1u, 1/4" CRA ≈ 33°		9569	5P	2.40	3.36	32.9	75.0	4.80	ok		
		9570	5P	2.00	3.80	32.6	75.5	4.77	ok		
		40084	4P	2.40	3.90	28.4	74.5	4.80	ok		
		40100	4P	2.40	3.38	32.9	75.6	4.80	ok		
		40108	4P	2.00	3.81	32.6	75.2	4.80	ok		
		40122	4P	2.20	4.2	31.1	72	4.90	ok		
		40129	4P	2.20	3.45	32.6	84.4	4.80	ok	From 40093	
		40145	4P	2.00	3.34	33.5	84.0	4.90	ok	40145A3/6 小頭	
	50030	5P	2.20	3.56	33.0	75.0	4.80	ok			
	50038	5P	1.80	4.1/3.8	33.3	81.5	4.90	ok			
40146	4P	2.40	3.40	31.9	88.4	4.80	ok	From 40103			
50190	5P	2.40	4.95	25.0	44.5	4.95	ok	Tele Lens			
OV08A10 1.0u, 1/4.4" CRA ≈ 16°											
13M	OV13855/13858 1.1u, 1/3.06" CRA ≈ 34° +/- 3	50013	5P	2.20	4.45	32.4	70.4	6.17	ok		
		50009C	5P	2.00	4.40	33.0	74.8	6.37	ok		
		50016	5P	2.00	4.50	32.0	75.0	6.17	ok		
		50018	5P	1.80	4.50	31.3	74.0	6.17	ok		
		9611	6P	2.00	4.60	31.6	75.0	6.37	ok		
		9614/16	6P	1.80	4.75	32.7	75.0	6.367	ok		
		9640	6P	2.00	4.30	33.7	77.0	6.37	ok		
		50061	5P	2.20	4.7	33.8	73.6	6.37	ok		
		50064B	5P	2.20	3.94	35	79.8	6.17	ok		
		50065B	5P	2.00	4.2	34.6	78.4	6.17	ok		
		50069B	5P	2.20	4.3	33.2	77	6.2	ok		
		50039B	5P	2.20	4.6	34.9	87.6	6.2	ok		
		40126	4P	2.20	4.45	33.8	79	6.20	ok		
		50113	5P	2.00	4.3	33.1	77.9	6.19	ok		
		50131	5P	2.20	3.74	35.2	83.8	6.10	ok		
		60000	6P	1.80	4.03	34.1	80.7	6.10	ok	From 9666	
		40153	4P	2.00	4.2	34	79.9	6.17	ok		

