



NO	Model	MAX Image Height	E.F.L	F/NO	FOV	FB	BFL	TTL	Element	Thread Size	Front end face diameter	Guide price
1	HK-6002	Ø3.5	1.20	2.00	Ø3.5=D=210°	3.23	4.22	25.10	6G	M25.4*P1.0	Ø20.0 Ø26.0	
					Ø3.2=D=176°					M12*P0.5		
					Ø3.0=D=160°							
2	HK-6003	Ø3.0	1.00	2.00	Ø3.0=D=236°	3.03	4.13	28.52	6G	M12*P0.5	Ø28.0 Ø32.0	
					Ø3.0=H=236°							
					Ø3.0=V=236°							
3	HK-6014	Ø3.20	1.10	2.00	Ø3.2 =D=190°	4.13	4.23	19.68	6G	M12*P0.5	Ø14.0	
4	HK-6016	Ø3.0	1.13	2.00	Ø3.1 =D=210°	3.18	3.41	17.12	6G	M12*P0.5	Ø16.0	
					Ø2.88 D=180°					M8.0*P0.5		
5	HK-6017	Ø5.4	1.90	2.50	Ø5.4 D=190°	3.68	4.79	21.29	6G	M12*P0.5	Ø17.0	
6	HK-6019	Ø3.2	1.10	2.00	Ø3.2 D=210°	2.85	3.75	28.51	6G	M12*P0.5	Ø32.0	
7	HK-6020	Ø3.0	1.05	2.00	Ø3.0 D=190°	3.28	4.19	21.73	7G	M12*P0.5	Ø27.00	
					Ø2.7 D=160°							
					Ø2.4 D=140°							
8	HK-6021	Ø3.10	1.13	2.00	Ø3.1 D=210°	3.18	3.41	17.12	6G	M12*P0.5	Ø17 Ø19	
9	HK-6023	Ø4.5	1.50	2.00	Ø4.5 D=220°	2.43	3.80	27.98	6G	M12*P0.5	Ø32	
10	HK-6024	Ø3.00	0.95	2.00	Ø3.0 D=220°	3.28	4.19	22.33	7G	M12*P0.5	Ø27	
11	HK-6026	Ø4.8	1.50	2.40	Ø4.8 D=200°	2.50	3.49	13.31	5G+1M	M12*P0.5	Ø14	
12	HK-6028	Ø6.3	1.90	2.50	Ø6.3 D=200°	3.58	4.34	17.75	5G2M	M12*P0.5	Ø18.5	
					Ø6.0 D=190°							
					Ø3.6 D=110°							
13	HK-6029	Ø5.4	2.40	2.40	Ø5.4 D=192°	4.40	4.80	19.12	4G	M12*P0.5	Ø15.0	
14	HK-6030	Ø3.5	1.65	2.50	Ø3.5 D=190°	4.11	4.45	19.44	4G	M12*P0.5	Ø15.0	
15	HK-6031	Ø5.0	1.60	2.50	Ø5.0 D=200°	2.80	3.69	14.20	5G1M	M12*P0.5	Ø14.0	
					Ø4.6 D=170°							
16	HK-6032	Ø4.5	1.52	2.40	Ø4.5 D=210°	3.77	3.97	20.70	5G1M	M12*P0.5	Ø27.0	
					Ø4.2 D=180°							
					Ø3.6 D=150°							
17	HK-6034	Ø3.2	1.00	2.00	Ø3.2 D=230°	2.70	3.64	28.79	5G+1M	M12*P0.5	Ø34.0	
					Ø3.1 D=210°							
					Ø2.9 D=187°							
18	HK-6036	Ø3.3	0.98	2.20	Ø3.3 D=220°	1.76	2.26	13.01	5G+1M	M12*P0.5	Ø18.5	
					Ø3.2 D=210°							
					Ø3.0 D=190°							
19	HK-6037	Ø3.0	1.40	2.40	Ø3.0 D=198°	2.37	3.18	19.38	4G	M12*P0.5	Ø27.0	
					Ø2.9 D=172°							
					Ø2.8 D=156°							

20	HK-6038	03.02	1.50	2.40	03.02 D=210°	1.72	2.38	14.52	6G	M8*P0.5	016.0 016.5	
					02.9 D=198°					M12*P0.5		
					02.8 D=190°							
21	HK-6039	04.0	1.36	2.00	04.0 D=240°	2.46	3.44	27.91	6G	M12*P0.5	032.0	
					03.8 D=200°							
					03.6 D=182°							
22	HK-6043B	05.2	1.80	2.40	D=190°	4.26	4.64	24.81	6G	M12*P0.5	017.0	
23	HK-6045	05.12	2.30	2.40	D=190°	3.33	4.73	23.93	4G	M12*P0.5	015.0	