



| NO | Model               | Sensor Size | MAX Image Height | E.F.L | F/NO | FOV    |         |         | FB   | BFL  | TTL            | Element | Thread Size | Front end face diameter   | Guide price |
|----|---------------------|-------------|------------------|-------|------|--------|---------|---------|------|------|----------------|---------|-------------|---|-------------|
|    |                     |             |                  |       |      | D      | H       | V       |      |      |                |         |             |   |             |
| 1  | HK-6026             | 1/4"        | Ø4.8             | 1.50  | 2.50 | D=182° | H=140°  | V=102°  | 2.50 | 3.49 | 13.31          | 5G+M1   | M12*P0.5    | Ø14.0<br>Ø12.0/Ø14.0<br>Ø14.0/Ø16台  |             |
|    |                     |             |                  |       |      |        |         |         |      |      |                |         | M8*P0.5     |   |             |
| 2  | HK-8001             | 1/3"        | Ø6.3             | 2.25  | 2.30 | D=170° | H=105°  | V= 84°  | 5.09 | 5.99 | 18.88          | 6G      | M12*P0.5    | Ø14.0<br>Ø15.0<br>Ø14.0/Ø16台  |             |
| 3  | HK-8012             | 1/4"        | Ø3.7             | 1.70  | 2.40 | D=170° | H=120°  | V= 95°  | 3.72 | 4.89 | 18.35          | 6G      | M12*P0.5    | Ø14.0<br>Ø14.0/Ø16台<br>Ø14.25/Ø16台  |             |
| 4  | HK-8015             | 1/3"        | Ø6.11            | 2.50  | 2.00 | D=120° | H=98°   | V=78°   | 3.29 | 4.28 | 20.76          | 4G      | M12*P0.5    | Ø15.0<br>Ø14.0/Ø16台<br>Ø14.0/Ø15.8槽   |             |
| 5  | HK-8025             | 1/3"        | Ø7.02            | 3.60  | 2.00 | D=92°  | H=70°   | V=53°   | 4.42 | 5.75 | 20.30          | 4G      | M12*P0.5    | Ø14.0   |             |
| 6  | HK-8047             | 1/4"        | Ø3.93            | 2.10  | 2.50 | D=130° | H=90°   | V=70°   | 3.19 | 3.95 | 14.87          | 4G      | M12*P0.5    | 14  |             |
| 7  | HK-8055<br>HK-8055B | 1/3"        | Ø6.1             | 2.35  | 2.50 | D=170° | H=110°  | V= 90°  | 3.74 | 4.19 | 13.34<br>13.70 | 5G      | 12*P0.5     | Ø10.0<br>Ø14.0<br>Ø9.0/Ø10.0台<br>Ø10.0/Ø14.0台<br>Ø12.0/Ø16.0台<br>Ø14.0/Ø16.0台<br>Ø14.0/Ø17.0台 |             |
|    |                     |             |                  |       |      |        |         |         |      |      |                |         | M8*P0.5     |   |             |
|    |                     |             |                  |       |      |        |         |         |      |      |                |         | M7*P0.35    |   |             |
| 8  | HK-8063             | 1/4"        | Ø5.3             | 2.50  | 2.50 | D=120° | H= 85°  | V= 65°  | 2.00 | 4.17 | 14.98          | 4G      | 12*P0.5     | Ø10.0<br>Ø14.0<br>Ø12.0/Ø14.0台<br>Ø14.0/Ø16.0台<br>Ø14.0/Ø17.0台<br>Ø14.25/Ø17.0台               |             |
|    |                     |             |                  |       |      |        |         |         |      |      |                |         | M8*P0.5     |   |             |
| 9  | HK-8064             | 1/4"        | Ø4.7             | 1.90  | 2.50 | D=160° | H= 100° | V= 80°  | 3.22 | 3.78 | 14.85          | 4G      | 12*0.5      | Ø10.0<br>Ø14.0<br>Ø12.9/Ø15.0台<br>Ø14.25/Ø16.0台<br>Ø14.0/Ø17.6台                               |             |
|    |                     |             |                  |       |      |        |         |         |      |      |                |         | M8*P0.5     |   |             |
| 10 | HK-8065             | 1/4"        | Ø4.47            | 1.70  | 2.50 | D=170° | H= 100° | V= 75°  | 3.71 | 4.27 | 18.60          | 4G      | M12*P0.5    | Ø14.0<br>Ø12.9/Ø14.0<br>Ø14.0/Ø16.0   |             |
| 11 | HK-8067-A           | 1/3"        | Ø5.04            | 1.75  | 2.50 | D=190° | H=170°  | V= 140° | 2.20 | 2.77 | 14.52          | 5G      | M12*P0.5    | Ø14.0<br>Ø14.0/Ø16.0  |             |
| 12 | HK-8067-B           | 1/4"        | Ø5.04            | 1.75  | 2.50 | D=176° | H=135°  | V=97°   | 1.97 | 2.54 | 14.52          | 5G      | M12*P0.5    | Ø14.0<br>Ø14.0/Ø16.0台   |             |

|    |           |        |       |      |      |        |        |        |      |      |       |      |           |   |
|----|-----------|--------|-------|------|------|--------|--------|--------|------|------|-------|------|-----------|---|
| 13 | HK-8067-C | 1/4"   | Ø4.9  | 1.75 | 2.50 | D=176° | H=135° | V=97°  | 2.93 | 3.50 | 16.42 | 5G   | M12*P0.5  | Ø14.0<br>Ø14.0/Ø16.0台<br>Ø13.9//Ø16.9                         |
| 14 | HK-8067-D | 1/3.2" | Ø5.04 | 1.75 | 2.50 | D=170° | H=120° | V=90°  | 2.20 | 2.77 | 14.52 | 5G   | M12*P0.5  | Ø14.0<br>Ø14.0/Ø16.0台   |
| 15 | HK-8067-E | 1/3"   | Ø5.04 | 2.00 | 2.50 | D=170° | H=130° | V=92°  | 2.20 | 2.77 | 14.52 | 5G   | M12*P0.5  | Ø14.0<br>Ø13.9/Ø17<br>Ø14.0/Ø16.0台<br>Ø18.0/Ø21.0台            |
| 16 | HK-8067-F | 1/3"   | Ø5.04 | 1.75 | 2.50 | D=190° | H=170° | V=140° | 2.20 | 2.77 | 14.52 | 5G   | M12*P0.5  | Ø14.0/Ø16.0台  |
| 17 | HK-8077   | 1/4"   | Ø4.48 | 1.30 | 2.25 | D=180° | H=130° | V=100° | 2.29 | 2.99 | 12.19 | 6G   | M8*P0.5   | Ø12.5/Ø14.0<br>Ø13.8带槽<br>Ø13.2/Ø14.8台<br>Ø12.8<br>Ø14.0/Ø16台 |
|    |           |        |       |      |      |        |        |        |      |      |       |      | M10*P0.5  |   |
|    |           |        |       |      |      |        |        |        |      |      |       |      | M12*P0.5  |   |
| 18 | HK-8082   | 1/3"   | Ø4.85 | 2.50 | 2.50 | D=170° | H=105° | V=80°  | 1.89 | 2.80 | 11.47 | 3G1P | M12*P0.5  | Ø12.0/Ø13.0台<br>Ø11.92/Ø14.0<br>台<br>Ø14.0/Ø16.0台             |
| 19 | HK-8132   | 1/4"   | Ø5.37 | 2.10 | 2.50 | D=130° | H=85°  | V=60°  | 3.25 | 4.11 | 14.88 | 3G1P | M12*P0.5  | Ø14.0   |
| 20 | HK-8136   | 1/4"   | Ø4.86 | 1.80 | 2.40 | D=170° | H=105° | V=73°  | 2.56 | 3.55 | 18.73 | 4G   | M12*P0.5  | Ø14.0<br>Ø14.0/Ø16.0  |
| 21 | HK-8151   | 1/4"   | Ø4.7  | 1.75 | 2.50 | D=190° | H=180° | V=170° | 2.32 | 3.20 | 15.17 | 6G   | M12*P0.5  | Ø14.0<br>Ø14.0/Ø16.0台   |
| 22 | HK-8180   | 1/3"   | Ø6.5  | 3.20 | 2.60 | D=130° | H=90°  | V=70°  | 3.65 | 4.65 | 20.45 | 4G   | M12*P0.5  | Ø14.0<br>Ø15.0  |
| 23 | HK-8192   | 1/4"   | Ø3.5  | 1.30 | 2.40 | D=180° | H=180° | V=160° | 2.88 | 3.20 | 14.00 | 6G   | M12*P0.5  | Ø14.00<br>Ø14.00/Ø16台<br>Ø14.25/Ø17台                          |
| 24 | HK-8239   | 1/2.7" | Ø7.0  | 3.00 | 2.40 | D=155° | H=120° | V=62°  | 4.72 | 5.52 | 21.87 | 4G   | M12*P0.5  | Ø14.0<br>Ø17.40<br>Ø25.00<br>Ø17/Ø19台                         |
| 25 | HK-8255   | 1/3"   | Ø6.2  | 1.45 | 2.30 | D=180° | H=180° | V=140° | 2.46 | 3.16 | 12.80 | 6G   | M12*P0.5  | Ø14.0<br>Ø14/Ø16台   |
| 26 | HK-9036   | 1/3"   | Ø6.2  | 2.60 | 2.60 | D=150° | H=105° | V=75°  | 2.38 | 3.56 | 13.11 | 3G1P | M12*P0.5  | Ø14.0<br>Ø12.0/Ø14.0台<br>Ø14.00/Ø16台                          |
|    |           |        |       |      |      |        |        |        |      |      |       |      | M8.0*P0.5 |   |
| 27 | HK-9037   | 1/4"   | Ø4.74 | 2.40 | 2.60 | D=130° | H=85°  | V=65°  | 2.48 | 3.56 | 13.28 | 3G1P | M8*P0.5   | Ø12.0<br>Ø12.0/Ø14.0槽<br>Ø12.35/Ø14.0<br>台                    |
| 28 | HK-9049   | 1/4"   | Ø4.48 | 2.25 | 2.50 | D=130° | H=90°  | V=70°  | 2.25 | 3.17 | 12.84 | 2G2P | M8*P0.5   | Ø10.0   |
| 29 | HK-9055   | 1/4"   | Ø5.11 | 1.10 | 2.40 | D=140° | H=125° |        | 1.58 | 2.18 | 11.64 | 2G2P | M12*P0.5  | Ø14.0/Ø16.0台  |

|    |             |        |       |      |      |        |        |       |      |      |       |      |          |                                       |  |
|----|-------------|--------|-------|------|------|--------|--------|-------|------|------|-------|------|----------|---------------------------------------|--|
| 30 | HK-9069     | 1/4"   | Ø4.8  | 2.40 | 2.60 | D=138° | H=85°  | V=65° | 3.85 | 4.92 | 11.42 | 1G2P | M12*P0.5 | Ø14.0<br>Ø12.0/Ø14.0台<br>Ø14.0/Ø16.0台 |  |
|    |             |        |       |      |      |        |        |       |      |      |       |      | M8*P0.5  |                                       |  |
| 31 | HK-9073     | 1/3"   | Ø5.72 | 1.70 | 2.60 | D=144° | H=120° | V=74° | 2.38 | 2.93 | 12.73 | 2G2P | M12*P0.5 | Ø12.0<br>Ø14.0<br>Ø12.0/Ø14.0台        |  |
|    |             |        |       |      |      |        |        |       |      |      |       |      | M8*P0.5  |                                       |  |
| 32 | HK-9075     | 1/3.7" | Ø4.94 | 2.20 | 2.60 | D=160° | H=110° | H=80° | 2.18 | 3.01 | 12.87 | 1G3P | M12*P0.5 | Ø13.8帶槽<br>Ø14.0<br>Ø14.0/Ø16.0台      |  |
|    |             |        |       |      |      |        |        |       |      |      |       |      | M8*P0.5  |                                       |  |
| 33 | HK-9089AS-A | 1/4"   | Ø5.2  | 1.30 | 2.60 | D=125° | H=110° | V=91° | 2.10 | 2.82 | 13.39 | 2G2P | M8*P0.5  | Ø12.0/Ø14.0台                          |  |
| 34 | HK-9148     | 1/4"   | Ø4.9  | 2.00 | 2.50 | D=140° | H=90°  | V=70° | 1.80 | 2.80 | 9.18  | 3G1P | M7XP0.35 | Ø10.0<br>Ø12.0/Ø14.0台                 |  |
|    |             |        |       |      |      |        |        |       |      |      |       |      | M8*P0.5  |                                       |  |
| 35 | HK-9165     | 1/4"   | Ø4.55 | 1.30 | 2.80 | D=160° | H=128° | V=96° | 1.66 | 2.26 | 9.78  | 2G2P | M7*P0.35 | Ø10.0<br>Ø12.0/Ø14.0台                 |  |
|    |             |        |       |      |      |        |        |       |      |      |       |      | M8*P0.5  |                                       |  |
| 36 | HK-9165B-   | 1/6"   | Ø4.55 | 1.30 | 2.80 | D=100° | H=85°  | V=70° | 1.66 | 2.26 | 9.78  | 2G2P | M8*P0.5  | Ø12.0/Ø14.0台                          |  |