



Fuzhou ChuangAn Optics Co., Ltd

Add: #43, Section C, Software Park, Fuzhou, China, 350003

Tel: 86-591-87880861 Fax: 86-591-87880862 Email: sandra.zhang@chancctv.com

Web: www.chancctv.com and www.visionlens.com

车载前视镜头 Front View Lens

规格型号	焦距	F-值	接口	靶面	光学后焦	机械后焦	总长	外形尺寸	视场角	像素	镜片结构	红外滤光片	备注
Model	EFL (mm)	F-NO	Mount	Image Size	BFL (mm)	FFL (mm)	TTL (mm)	Dimension	Field of View (H*V*D)	Resolution	Structure	IR Cut Filter	Remarks
CA389B	2.67	1.8	M12*P0.5	1/2.9"	5.09	3.86	21.71	φ14*L17.85	130°*65.7°*160°	MP	6G	Yes	support IP67-IP69
CA389C	2.67	1.8	M12*P0.5	1/2.9"	5.09	3.86	21.71	φ14*L17.85	130°*65.7°*160°	MP	6G	No	support IP67-IP69
CA389G	2.67	1.8	M12*P0.5	1/2.9"	5.09	3.90	21.71	φ14*L17.81	130°*65.7°*160°	MP	6G	Yes	support IP67-IP69
CA343A	2.95	2.0	M12*P0.5	1/2.7"	5.83	4.65	20.80	φ14*L16.15	118°*62°*140°	5MP	5G	Yes	support IP67-IP69
CA343B	2.95	2.0	M12*P0.5	1/2.7"	5.83	4.65	20.80	φ14*L16.15	118°*62°*140°	5MP	5G	No	support IP67-IP69
CA343C	2.95	2.0	M12*P0.5	1/2.7"	5.83	4.65	20.80	φ14*L16.15	118°*62°*140°	5MP	5G		650-940nm dualpass filter
CA390E	2.76	2.4	M12*P0.5	1/3"	5.08	4.19	20.50	φ14*L16.31	126°*70°*158°	MP	6G	No	AR coating/ support IP67-IP69
CA390F	2.76	1.9	M12*P0.5	1/3"	5.08	4.23	20.50	φ14*L16.27	126°*70°*158°	MP	6G	No	AR coating/ support IP67-IP69
CA390H	2.76	1.9	M12*P0.5	1/3"	5.08	4.23	20.50	φ14*L16.27	126°*70°*158°	MP	6G	Yes	AR coating/ support IP67-IP69
CA3544C	2.78	2.0	M12*P0.5	1/2.7"	4.69	3.62	17.68	φ14*L14.06	108°*76°*140°	6MP	6G	Yes	support IP67-IP69
CA3544D	2.78	2.0	M12*P0.5	1/2.7"	4.69	3.62	17.68	φ15*L14.06	108°*76°*140°	6MP	6G	Yes	support IP67-IP69

车载后视镜头 Rear View Lens

规格型号	焦距	F-值	接口	靶面	光学后焦	机械后焦	总长	外形尺寸	视场角	像素	镜片结构	红外滤光片	备注
Model	EFL (mm)	F-NO	Mount	Image Size	BFL (mm)	FFL (mm)	TTL (mm)	Dimension	Field of View (H*V*D)	Resolution	Structure	IR Cut Filter	Remarks
CA358A	1.75	2.0	M12*P0.5	1/4"	4.35	3.49	18.5	φ14*L15.01	128°*95°*170°	MP	6G	Yes	support IP67-IP69
CA367B	1.5	2.0	M12*P0.5	1/3.6"	3.6	2.30	18.9	φ17*L16.55	139°*100°*175°	MP	6G	Yes	support IP67-IP69
CA364B	1.73	2.0	M12*P0.5	1/2.7"	3.32	2.71	14.51	φ16*L11.8	190°*145°*200°	MP	6G	Yes	support IP67-IP69

CA364D	1.73	2.0	M12*P0.5	1/2.7"	3.32	2.71	14.51	φ14*L11.8	190°*145°*200°	MP	6G	Yes	support IP67-IP69
CA364E	1.73	2.0	M12*P0.5	1/2.7"	3.32	2.71	14.51	φ16*L11.8	190°*145°*200°	MP	6G	No	support IP67-IP69
CA341A	1.83	2.0	M12*P0.5	1/2.7"	4.61	3.81	17.01	φ16*L13.20	160°*105°*190°	MP	6G	Yes	support IP67-IP69
CA341B	1.83	2.0	M12*P0.5	1/2.7"	4.61	3.81	17.01	φ14*L13.20	160°*105°*190°	MP	6G	Yes	support IP67-IP69

车载环视镜头 Surround View Lens

规格型号	焦距	F-值	接口	靶面	光学后焦	机械后焦	总长	外形尺寸	视场角	像素	镜片结构	红外滤光片	备注
Model	EFL (mm)	F-NO	Mount	Image Size	BFL (mm)	FFL (mm)	TTL (mm)	Dimension	Field of View (H*V*D)	Resolution	Structure	IR Cut Filter	Remarks
CA3596A	1.30	1.8	M12*P0.5	1/3"	3.06	2.16	13.0	φ16.0*L10.84	220°*130°*230°	MP	6G+IMO	Yes	All Glass/ support IP67-IP69
CA3597A	1.60	2.0	M12*P0.5	1/4"	3.26	2.08	14.8	φ14*L12.72	141°*103°*185°	MP	6G	Yes	support IP67-IP69
CA3597B	1.60	2.0	M10*P0.5	1/4"	3.26	2.08	14.8	φ14*L12.72	141°*103°*185°	MP	6G	Yes	support IP67-IP69
CA3598A	1.27	2.2	M8*P0.5	1/4"	3.02	2.29	12.2	φ12*L9.93	130°*95°*180°	MP	6G	Yes	support IP67-IP69
CA347A	1.48	2.0	M12*P0.5	1/4"	2.69	2.10	16.6	φ17.5*L14.5	180°*133°*200°	MP	8G	Yes	support IP67-IP69
CA3615A	1.00	2.0	M12*P0.5	1/4"	2.11	1.23	13.0	φ14*L11.72	188°*144°*200°	MP	4G2P	Yes	support IP67-IP69

行车记录仪镜头 Dash Camera Lens

规格型号	焦距	F-值	接口	靶面	光学后焦	机械后焦	总长	外形尺寸	视场角	像素	镜片结构	红外滤光片	备注
Model	EFL (mm)	F-NO	Mount	Image Size	BFL (mm)	FFL (mm)	TTL (mm)	Dimension	Field of View (H*V*D)	Resolution	Structure	IR Cut Filter	Remarks
CA1300A	2.92	2.4	M12*P0.5	1/2.5"	5.26	3.64	13.97	φ14*L10.33	115°*71°*145°	MP	5G	Yes	support IP67-IP69
CA1300B	2.92	2.4	M8*P0.35	1/2.5"	5.26	3.64	13.97	φ10*L10.33	115°*71°*145°	MP	5G	Yes	support IP67-IP69
CA1303A	3.53	2.4	M12*P0.5	1/2.7"	6.18	3.64	13.97	φ14*L10.33	109°*55°*138°	MP	5G	Yes	support IP67-IP69
CA1304A	3.53	2.4	M8*P0.35	1/2.7"	5.26	4.00	13.97	φ10*L9.97	109°*55°*138°	MP	5G	Yes	support IP67-IP69
CA1305A	3.65	2.4	M12*P0.5	1/2.5"	5.75	4.52	13.97	φ14*L10.92	100°*53°*120°	MP	5G	Yes	support IP67-IP69
CA1306A	3.65	2.4	M8*P0.35	1/2.5"	5.75	3.58	13.97	φ10*L10.4	100°*53°*120°	MP	5G	Yes	support IP67-IP69
CA1307B	2.3	2.4	M10*P0.5	1/4"	4.33	2.60	12.85	φ14*L10.25	98°*70°*138°	MP	5G	Yes	support IP67-IP69

CA1307D	2.3	2.4	M12*P0.5	1/4"	4.33	2.60	12.85	φ14*L10.25	98*70*138°	MP	5G	Yes	support IP67-IP69
CA1307G	2.3	2.4	M8*P0.35	1/4"	4.33	2.60	12.85	φ11*L10.25	98*70*138°	MP	5G	Yes	support IP67-IP69
CA1308B	2.0	2.4	M8*P0.5	1/4"	4.01	2.38	13.06	φ10.5*L10.68	115*87*170°	MP	5G	Yes	support IP67-IP69
CA1308C	2.0	2.4	M8*P0.5	1/4"	4.01	2.38	13.06	φ12*L10.68	115*87*170°	MP	5G	No	support IP67-IP69
CA1309A	2.0	2.4	M10*P0.5	1/4"	4.01	2.44	13.06	φ12*L10.62	115*87*170°	MP	5G	Yes	support IP67-IP69
CA1309B	2.0	2.4	M10*P0.5	1/4"	4.01	2.44	13.06	φ12*L10.62	115*87*170°	MP	5G	No	support IP67-IP69
CA1310A	2.0	2.4	M12*P0.5	1/4"	5.26	2.49	13.06	φ14*L10.57	115*87*170°	MP	5G	Yes	support IP67-IP69
CA3600A	2.26	2.0	M7*P0.35	1/4"	5.09	3.86	9.32	φ8.0*L7.81	112*78*140°	MP	2G2P	Yes	support IP67-IP69

自动驾驶镜头 ADAS Lens

规格型号	焦距	F-值	接口	靶面	光学后焦	机械后焦	总长	外形尺寸	视场角	像素	镜片结构	红外滤光片	备注
Model	EFL (mm)	F-NO	Mount	Image Size	BFL (mm)	FFL (mm)	TTL (mm)	Dimension	Field of View (H*V*D)	Resolution	Structure	IR Cut Filter	Remarks
CA2796A	6	2.8	M12*P0.5	1/2.7"	6.86	5.6	22.45	Φ14*16.85	38°*22°*43°	MP	7G	Yes	support IP67-IP69
CA2796B	6	6.0	M12*P0.5	1/2.7"	6.86	5.6	22.45	Φ14*16.85	38°*22°*43°	MP	7G	Yes	support IP67-IP69
CA3599A	5.4	2.0	M12*P0.5	1/2.7"	8.20	7.18	17.02	φ14.0*L9.84	59°*33°*68.8°	MP	5G	Yes	support IP67-IP69
CA3599B	5.4	2.0	M12*P0.5	1/2.7"	8.20	7.18	17.02	φ14.0*L9.84	59°*33°*68.8°	MP	5G	Yes	support IP67-IP69
CA2698A	3.57	2.5	M12*P0.5	1/2.3"	4.50	3.31	16.31	Φ14*13.00	108°*81°*135°	4K	4G+2MO	Yes	All Glass/ support IP67-IP69
CA2698B	3.57	2.5	M12*P0.5	1/2.3"	4.50	3.31	16.31	Φ14*13.00	108°*81°*135°	4K	4G+2MO	No	All Glass/ support IP67-IP69