



NO	Model	Sensor Size	MAX Image Height	E.F.L	F/NO	FOV	FB	BFL	TTL	Element	Thread Size	Front end face diameter	Guide price
1	HK-8110	1/2.5"	Ø7.2	3.00	2.80	D=160°	4.28	4.96	14.51	3G1P	M8*P0.5	Ø10.0 Ø14.0	
						H=106°					M12*P0.5		
2	HK-8121	1/2.5"	Ø7.2	2.50	2.80	D=160°	4.79	5.29	23.57	6G	M12*P0.5	Ø10.0 Ø14.0 Ø17.0	
						H=125°					M8*P0.5		
3	HK-8133	1/3"	Ø6.0	2.70	2.80	D=160°	4.54	5.08	14.82	5G	M12*P0.5	Ø12.0 Ø14.0	
						H=110°							
						V=80°							
4	HK-8134	1/2.7"	Ø7.0	3.20	2.80	D=140°	4.46	5.01	13.97	5G	M12*P0.5	Ø10.0 Ø14.0	
						H=100°					M8*P0.5		
											M7*P0.5		
5	HK-8141	1/4"		3.56	2.80	D=80°	4.39	5.24	15.03	4G	M12*P0.5	Ø14.0	
						H=60°							
6	HK-8173	1/4"	Ø4.66	2.30	2.40	D=190°	2.46	4.01	12.76	5G	M7*P0.5	Ø10.0 Ø11.0 Ø14.0	
											M8*P0.5		
											M12*P0.5		
7	HK-8181	1/2.5"		3.10	2.00	D=170°	5.08	5.98	20.55	6G	12*P0.5	Ø10.0 Ø14.0 Ø15.0 Ø17.5 Ø25.0	
						H=120°							
8	HK-8205	1/2.5"	Ø7.5	3.60	2.00	D=120°	5.20	7.20	22.49	6G	M12*P0.5	Ø14.0	
						H=88°							
						V=55°							
9	HK-8209	1/2.8"	Ø6.8	2.60	2.20	D=170°	4.42	5.39	23.33	7G	M12*P0.5	Ø17.0	
						H=130°							
						V=105°							
10	HK-8222	1/2.3"	Ø8.4	3.00	2.50	D=170°	4.35	6.35	23.41	7G	M12*P0.5	Ø17.0 Ø17.4 Ø18.0	
						H=130°							
11	HK-8236	1/2.7"	Ø7.0	3.80	2.80	D=100°	6.88	7.78	19.95	6G	M12*P0.5	Ø14.0	
						H=86°							
						V=50°							
12	HK-8244E	1/2.7"	Ø6.94	3.00	2.50	D=160°	3.70	6.04	17.17	6G	M8*P0.5	Ø11.5 Ø15.0	
						H=120°					M12*P0.5		
						V=60°							

13	HK-8247	1/2.3"	Ø8.2	3.40	2.80	D=150°	5.33	6.30	17.40	5G+1M	M12*P0.5	Ø14.0 Ø15.0 Ø17.0	
						H=110°					M12*P0.5		
						V= 83°							
14	HK-8253	1/5.8"	Ø3.2	1.90	2.20	D=120°	2.10	3.23	21.93	4G	M12*P0.5	Ø17.0	
						H= 90°					M12*P0.5		
						V= 65°							
15	HK-8268	1/2.3"	Ø8.3	3.20	2.20	D=170°	6.31	7.09	23.90	7G	M12*P0.5	Ø17.0	
						H=120°					M12*P0.5		
						V= 85°							
16	HK-8271		Ø7.3	3.40	2.40	D=140°	3.88	5.13	14.48	5G	M8.5*P0.5	Ø10.0 Ø12.0	
						H=104°					M12*P0.5		
						V=60°							
17	HK-8276	1/2.7"	Ø7.0	3.00	2.40	D=155°	4.72	5.52	21.87	4G	M12*P0.5	Ø17.4 Ø25.0	
						H=120°					M12*P0.5		
						V= 62°							
18	HK-8277	1/2.7"	Ø6.2	3.26	2.20	D=126°	4.66	5.56	17.82	4G	M12*P0.5	Ø14.0	
						H= 104°					M12*P0.5		
						V= 54.5°							
19	HK-8278	1/2.7"	Ø6.8	3.30	1.30	D=160°	4.92	6.31	22.71	7G	M12*P0.5	Ø14.0	
						D=115°					M12*P0.5		
						D=58°							