

GSEO Product List

Update: 2018/07/06

Type	Size	Sensor	Pixel Size	IC	Product	MIC	Process	Config	RI	MBFL	IRF	TTL	FOV	F/NO	CRA	Thread	Holder / VCM	Status			
																		Designing	Tooling	Sample	MP
2M	1/3.4"	OV9282	3.0u	5.21	GS-8979AA	5.30	COB	4P	24.1	0.91	0.30	4.30	91.5	1.9	30.7	/	Unibody			V	
	1/5"	OV02A10	1.75u	3.50	GS-8900CA	3.80	COB	3P	33.8	0.75	0.21	3.00	78.2	2.4	30.3	M4.9*0.2P			V		
4M	1/3"	OV4688	2.0u	6.18	GS-8768DA	6.45	COB	5P	25.5	0.85	0.21	4.13	81.0	2.0	34.0	M6.5*0.25P	7.7*8.45			V	
				6.18	GS-8768GA	6.45	COB	5P	25.5	0.85	0.21	4.13	81.0	2.0	34.0	M6.5*0.25P	7.55*8.45			V	
5M	1/4"	OV5647/93/95	2.0u	4.54	GS-8670AA	4.74	COB	4P	43.0	1.10	0.30	4.15	65.80	2.4	24.4	M6*0.25P	TDK 606			V	
				4.54	GS-8753AA	4.90	COB	5P	34.1	0.75	0.21	4.10	80.6	2.0	31.5	M6*0.25P	8.45x8.45			V	
		OV5693/95	4.54	GS-8830AA	4.80	COB	4P	39.7	0.80	0.21	3.81	74.2	2.0	32.9	M6*0.25P	6.5*6.5			V		
			4.54	GS-8791AA	4.80	COB	5P	26.4	0.65	0.21	4.10	88.0	2.0	31.7	M6*0.25P	7*7			V		
		OV5648/93/95	4.54	GS-8719AA	4.90	COB	5P	31.0	0.78	0.21	4.00	94.60	2.4	32.5	M5.5*0.25P	6.5*6.5			V		
		OV5648/93/95	4.54	GS-8701BA	4.83	COB	4P	47.8	0.90	0.21	3.68	71.00	2.4	31.0	M6*0.35P	Shicoh Z11 / TDK 608 / XPT S320 (PLCC type)			V		
		OV5693/95	4.54	GS-8793AA	4.80	COB	4P	41.1	0.80	0.21	3.80	74.6	2.0	31.1	M6*0.25P			V			
		OV5648/93/95	4.54	GS-8891EA	4.84	COB	3P	37.5	0.84	0.21	4.50	78.3	2.4	32.5	M6*0.2P			V			
	OV5648/93/95	4.54	GS-8848AA	4.85	COB	4P	29.3	0.90	0.21	3.34	83.6	2.0	33.6	M5.5*0.2P			V				
	1/5"	OV5675	1.12u	3.63	GS-8882AA	3.90	COB	5P	30.1	0.60	0.11	3.92	120.0	2.2	31.8	M4.5*0.25P			V		
8M	1/3.2"	OV8825/30/65	1.4u	5.71	GS-8787AA	6.17	COB	5P	37.6	1.04	0.21	4.40	75.8	2.2	32.0	M6.5*0.25P	TDK 658ABJ / MTM L3			V	
				5.74	GS-8833AA	6.17	COB	5P	34.6	0.80	0.21	4.10	78.7	2.0	32.7	M6.5*0.25P					
				5.74	GS-8833BA	6.17	COB	5P	34.6	0.80	0.21	4.22	78.4	2.0	33.2	M6.5*0.25P			V		
	1/4"	OV8850/55/56/58	1.12u	4.60	GS-8744BA	4.83	COB	4P	44.2	0.90	0.21	3.68	71.0	2.4	31.2	M6*0.35P	TDK 607ABA / TDK 608ABA			V	
		OV8855/56/58		4.57	GS-8837DA	4.85	COB	4P	28.1	0.90	0.21	3.34	84.0	2.0	33.6	M5.5*0.20P			V		
OV8855/56/58	4.57	GS-8938AA	4.85	COB	4P	28.1	0.90	0.21	3.39	84.0	2.0	33.6	/	Unibody			V				
13M	1/3.06"	OV13851/50/53/55/58	1.12u	5.87	GS-8814BA	6.17	COB	5P	44.3	1.10	0.21	5.00	69.20	2.0	32.7	M6.5*0.25P			V		
				5.87	GS-8725AA	6.17	COB	5P	36.9	1.01	0.21	4.45	77.20	2.2	32.1	M6.5*0.25P	TDK 658ABJ / MTM L3			V	
				5.87	GS-8802AA	6.17	COB	5P	33.3	0.80	0.21	4.22	78.70	2.0	33.8	M6.5*0.25P			V		
				5.87	GS-8836BA	6.10	COB	5P	33.0	0.80	0.21	3.95	80.00	2.2	34.5	M6.5*0.25P			V		
				5.87	GS-8816AA	6.17	COB	5P	36.9	1.01	0.21	4.45	77.20	2.0	32.1	M6.5*0.25P	TDK 658ABJ			V	
16M	1/3.06"	OV16880 / OV16885	1.0u	5.79	GS-8834AA	6.17	COB	5P	34.1	0.80	0.21	4.22	80.1	2.0	32.7	M6.5*0.25P			V		
				5.79	GS-8834EA	6.17	COB	5P	30.8	0.80	0.21	4.10	80.1	2.0	33.2	M6.5*0.25P			V		
				5.76	GS-8985AA	6.06	COB	6P	25.5	0.90	0.21	5.12	117.0	2.2	35.5	M6.8*0.25P	7.9*7.9			V	
20M	1/2.8"	OV20880	1.0u	6.37	GS-8968BA	6.80	COB	6P	32.3	0.85	0.21	4.6	76.9	1.8	34.0	M6.8*0.25P	TVF-6802DA MTM KAFV82VS88-CA			V	