


Dual Frequency Ultra-Low Phase Jitter Digitally Synthesized Oscillators (DSO)

Features

- Factory Programmable
 - Any frequency from 10 MHz to 1000 MHz
 - Differential Output: CML/LVDS/LVPECL/LVDS-EXT/HCSL
- Ultra-Low RMS phase jitter (12 KHz to 20 MHz)
 - 35 fs at 156.25 MHz
 - 25 fs at 312.50 MHz
 - 26 fs at 491.52 MHz
 - 27 fs at 625 MHz
- Total stability of ± 20 ppm
- Output Enable/Disable Feature
- < 10 ms start-up time
- No activity dips or micro jumps
- FS Pin: Supports 2 Frequencies
- Standard 2.5X2.0 mm, 2.0X1.6 mm 6-pin LGA package
- 1.8V supply with internal regulator
- Superior power supply immunity
- Industrial Temperature range: -40°C to 85°C
- Extended Temperature range: -40°C to 105°C
- ESD HBM 2000V, CDM 500V
- Lead free / RoHS compliant

Applications

- Network Equipment (Optical Modules, routers)
- 100G/200G/400G/800G/1.6T/3.2T OTN, Coherent optics
- Storage, switches, servers, NICs, accelerators
- 3G to 24G SDI broadcast video
- 10G/40G/100G optical ethernet
- 112G/224G/448G PAM4 Clocking
- Test and measurement equipment



General Description

The MS1133/MS1183 is a digitally synthesized oscillator (DSO) that combines advanced Bulk Acoustic Wave (BAW) resonator technology with high-performance digital frequency synthesis to deliver highly stable, fully programmable multi-GHz clocks with extremely low phase jitter.

Built-in Adaptive Intelligence continuously monitors operating conditions in the background, using autonomous DSP algorithms to maintain robust and consistent performance across process, voltage, and temperature.


The devices are factory programmed to provide an accurate frequency between 10 MHz and 1000 MHz at less than 1 ppb resolution.


The MS1133/MS1183 is manufactured in a high-volume 28 nm CMOS process and represents the most advanced node in the timing industry.

Device Information

Part Number	Package	Description
MS1133	2.5x2.0 mm 6-pin LGA	Dual Freq Oscillator
MS1183	2.0x1.6 mm 6-pin LGA	Dual Freq Oscillator

Figure 1. Functional Block Diagram



MS1133/MS1183**Pin Assignment and Pin Description (TOP VIEW)****Figure 2. MS1133/MS1183 Pin Assignments****Table 1. MS1133/MS1183 Pin Descriptions**

Pin No	Name	Description
1	OE	Output Enable - High/Floating: Output enabled (Internal pull-up of 100kΩ) - Low: Output disabled
2	FS	Frequency Select FS=1 or NC: Frequency 1 FS=0: Frequency 2
3	GND	Ground
4	CLK+	True Clock Output
5	CLK-	Complementary Clock Output
6	VDD	Power Supply – connect bypass capacitor between this pin and pin 3. Keep bypass as close as possible to the pins

Part Ordering Information

Figure 3 shows a logic tree for ordering each of the available parts.




Figure 3. MS1133/MS1183 Part Ordering Information

Table 2. Example of ordering part number

Base P/N	Output Format	Operating Temperature	Frequency Code 1	Frequency Code 2	Shipment Type	Ordering part number
1133	HCSL	-40°C to 85°C	156.25 MHz	312.5MHz	Tape and Reel	1133EA156M312R
1183	LVPECL	-40°C to 105°C	312.5 MHz	625MHz	Tape and Reel	1183DB312M625R

Input Frequency codes for ordering

Code (xxx/yyy)	Frequency (MHz)
010	10
100	100
106	106.25
122	122.88
153	153.6
156	156.25
212	212.5
245	245.76
250	250
307	307.2
312	312.5
322	322.2656525
491	491.52
500	500
614	614.4
625	625
644	644.53125
750	750

Please contact Mixed-Signal Devices for additional frequency codes

Specifications

Table 3. Electrical Specifications

Typical values are specified at $T_A = 25^\circ\text{C}$, $V_{DD} = 1.8\text{V}$ unless otherwise specified. All Min and Max limits are specified over the operating temperature range and voltage range with standard output terminations (See Figure 9-15). A 0.1 μF and 10 μF bypass capacitors should be connected between VDD and GND pins located close to the device.

Parameter	Symbol	Test Condition/Comment	Min	Typ	Max	Unit
-----------	--------	------------------------	-----	-----	-----	------

Frequency Range

Frequency Range	F_{CLK}	All Output Formats	10		1000	MHz
-----------------	-----------	--------------------	----	--	------	-----

Frequency Stability

Frequency Stability*	F_{STB}		-20		20	PPM
----------------------	-----------	--	-----	--	----	-----

*Frequency stability includes initial tolerance, voltage tolerance, operating temperature and aging (10 year, $+25^\circ\text{C}$). Aging is estimated from environmental reliability tests;

Clock Output Jitter Characteristics

RMS Phase Jitter (12 KHz – 20 MHz integration band)	Φ_{JITTER}	Frequency=312.5 MHz		25	37	fs
		Frequency=625 MHz		27	40	fs

Note:

Phase jitter measured on Agilent 5052B Signal Source Analyzer

Operating Voltage/Temperature Range

Supply Voltage	V_{DD}		1.71 (-5%)	1.8	1.89 (+5%)	V
Temperature Range	T_A	Industrial Temperature	-40	25	85	$^\circ\text{C}$
		Extended Industrial Temperature	-40	25	105	$^\circ\text{C}$

Current Consumption

Supply Current Consumption	I_{DD}	LVDS Output (Output Enabled)		80	100	mA
		All Other Outputs (Output Enabled)		90	110	mA
		Tristate Hi-Z (Output Disabled. OE=0)		50	60	mA

Input Characteristics

Digital Input Levels(OE//FS)	V_{IH}		$0.7XV_{DD}$			V
	V_{IL}				$0.3XV_{DD}$	V
Output Enable (OE)	T_D	Output Disable Time			3	μs
	T_E	Output Enable Time			20	μs
Powerup Time	T_{PWR}	Time from $0.9XV_{DD}$ until output frequency (F_{CLK}) within spec			10 Char data	ms

PSRR Characteristics

Power Supply-Induced Phase Noise	PSPN	Spurs induced by 50mV power supply ripples (1) (Center Frequency is 312.5MHz)		-110		dBc
Power Supply-Jitter Sensitivity	PSJS			0.2		fs/mV
Note: (1) Measured with 50 mVpp ripple from 500 KHz to 10 MHz applied on VDD Pin						

Output Characteristics

Output Duty Cycle	DC	All Output Formats	48		52	%
Output Rise/Fall Time (20% to 80% V_{PP})	T_R / T_F	All Output Formats		60	80	ps
CML Output (AC-Coupled)	V_{pp}	Differential Pk-Pk See Figure 9 , Figure 10	0.6	0.8	1	V
LVDS Output (AC-Coupled)	V_{pp}	Differential Pk-Pk See Figure 11	0.5	0.7	0.9	V
LVDS-EXT Output (AC-Coupled)	V_{pp}	Differential Pk-Pk See Figure 11	0.8	1.2	1.6	V
LVPECL Output (AC-Coupled)	V_{pp}	Differential Pk-Pk See Figure 12 , Figure 13	1.2	1.4	1.6	V
HCSL Output (AC or DC-Coupled)	V_{pp}	Differential Pk-Pk See Figure 14 , Figure 15	1.1	1.35	1.6	V
HCSL Output Voltage (DC- Coupled)	V_{CM}	Common Mode Voltage	340	350	360	mV

Unless otherwise specified, all differential output amplitudes are measured across a 100 Ω differential load or the termination network shown in the referenced output driver figures on the following pages

Table 4. Absolute Maximum Ratings

Parameter	Min	Max	Unit
1.8V Supply Voltage	-0.3	1.98	V
Digital I/O (OE/FS)	-0.3	1.98	V
Maximum Operating Temperature		105	°C
Storage Temperature	-55	150	°C
Junction Temperature		150	°C
Note: Stresses that exceed what is listed in this table may cause permanent damage to the device. Exposure to conditions above the recommendations for extended periods of time may affect device reliability.			

Table 5. Environmental Compliance

Parameter	Test Condition	Value	Unit
Moisture Sensitivity Level (MSL)	MSL3 @260°C		
Soldering Temperature	MIL-STD-883, Method 2003	260	°C
Electrostatic Discharge (HBM)	JEDEC JS-001	2000	V
Charge-Device Model (CDM)	JEDEC JESD22-C101	500	V
Latch-up Compliance	JESD78 Compliant		

Table 6. Package Thermal Information

Package	Parameter	Symbol	Value	Unit
2.5mm x 2mm 6 pin LGA	Maximum Board Temperature	T _B	125	°C
	Thermal Resistance, Junction to Ambient	θ _{JA}	90	°C/W
	Thermal Resistance, Junction to Board	θ _{JB}	40	°C/W
	Air Flow Condition		0	mps
	Maximum Junction Temperature	T _J	125	°C
Note: The thermal resistance information stated in this table is based on a standard JEDEC PCB condition. The actual thermal resistance varies depending on the customer PCB design.				

Table 7. Package Thermal Information

Package	Parameter	Symbol	Value	Unit
2.0mm X 1.6mm 6 pin LGA	Maximum Board Temperature	T _B	125	°C
	Thermal Resistance, Junction to Ambient	θ _{JA}	110	°C/W
	Thermal Resistance, Junction to Board	θ _{JB}	60	°C/W
	Air Flow Condition		0	mps
	Maximum Junction Temperature	T _J	125	°C
Note: The thermal resistance information stated in this table is based on a standard JEDEC PCB condition. The actual thermal resistance varies depending on the customer PCB design.				

Table 8. Typical Output Phase Noise CharacteristicsVDD= 1.8V, T_A = 25°C, Output Type = LVDS-EXT

Offset frequency	156.25 MHz	312.50 MHz	491.52 MHz	625 MHz	Unit
1 KHz	-106	-103	-100	-98	dBc/Hz
10 KHz	-138	-133	-128	-127	dBc/Hz
100 KHz	-157	-154	-149	-147	dBc/Hz
1 MHz	-167	-163	-158	-156	dBc/Hz
10 MHz	-168	-164	-160	-148	dBc/Hz
20 MHz	-168	-164	-159	-158	dBc/Hz
RMS Jitter (12 KHz – 20 MHz)	35	25	26	27	fs

Typical Output Measured Phase Noise Plots

This section shows MS1133/MS1183 performance plots.

Measurement parameters are: VDD = 1.8 V, TA = 25°C, Output Type = LVDS-EXT.

The plots were captured using an Agilent E5052B Signal Source Analyzer.




Figure 4. Center Frequency: 156.25 MHz




Figure 5. Center Frequency: 312.5 MHz




Figure 6. Center Frequency: 491.52 MHz




Figure 7. Center Frequency: 625 MHz

Output Terminations

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
CML	0.8V	AC	100 Ω diff
LVDS	0.7V	AC	100 Ω diff
LVDS-EXT	1.2V	AC	100 Ω diff
LVPECL	1.4V	AC	50 Ω to VT
LVPECL (DC Bias Resistor)	1.4V	AC	150 Ω to 250 Ω to GND, 50 Ω to VT
HCSL (Int Term)	1.35V	AC or DC	None
HCSL	1.35V	DC	50 Ω to GND




Figure 8. Differential Output Swing




Figure 9. CML Output Driver with 100 Ω Differential Receiver Termination

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
CML	0.8V	AC	100 Ω diff




Figure 10. CML Output Driver with 100 Ω Differential Receiver Termination

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
CML	0.8V	AC	100 Ω diff




Figure 11. LVDS/LVDS-EXT Output Driver with 100 Ω Differential Termination

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
LVDS/LVDS-EXT	0.7V/1.2V	AC	100 Ω diff




Figure 12. LVPECL Output Driver with External VT Bias Termination

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
LVPECL	1.4V	AC	50Ω to VT




Figure 13. LVPECL Output Driver with Source Bias Resistors and External VT Bias Termination

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
LVPECL (DC Bias Resistor)	1.4V	AC	150 Ω to 250 Ω to GND, 50 Ω to VT




Figure 14. HCSL Output Driver with Integrated Termination to Ground

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
HCSL (Int Term)	1.35V	AC/DC	None




Figure 15. HCSL Output Driver with 50 Ω Receiver Termination to Ground

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
HCSL	1.35V	DC	50 Ω to GND

Output Timing




Figure 16. Output Timing across differential pair (CLK_p - CLK_n)

Parameter	Symbol	Test Condition/Comment	Min	Typ	Max	Unit
Output Duty Cycle	DC	All Output Formats	48		52	%
Output Rise/Fall Time (20% to 80% V _{PP})	T _R / T _F	All Output Formats		60	80	ps




Figure 17. HCSL Output Level across differential pair (CLK_p - CLK_n)

Parameter	Symbol	Test Condition/Comment	Min	Typ	Max	Unit
HCSL Output Voltage (DC- Coupled)	V _{CM}	Common Mode Voltage	340	350	360	mV




Figure 18. Powerup Timing

Parameter	Symbol	Test Condition/Comment	Min	Typ	Max	Unit
Powerup Time	T_{PWR}	Time from 0.9xVDD until output frequency (F_{CLK}) within spec			10	ms




Figure 19. OE Enable/Disable Timing

Parameter	Symbol	Test Condition/Comment	Min	Typ	Max	Unit
Output Enable (OE)	T_D	Output Disable Time			3	μ s
	T_E	Output Enable Time			20	μ s

Packaging Information

Figure 20 shows the MS1133 packaging drawing




Figure 20. MS1133 Packaging Drawing (2.5X2.0 mm)

Table 9. MS1133 Packaging Dimensions

Dimensions	Min	Nom	Max
A	2.00 BSC		
B	2.50 BSC		
C	0.86	0.96	1.06
L	0.55	0.60	0.65
W	0.35	0.40	0.45
D	0.85 BSC		
E	1 BSC		
Package Edge Tolerance	0.1		
Mold Flatness	0.2		
Coplanarity	0.08		

Note: All dimensions are in millimeters

Packaging Land Pattern

Figure 21 shows the MS1133 PCB land pattern.
Note: All dimensions are in millimeters




Figure 21. MS1133 Packaging Land Pattern Drawing (2.5X2.0 mm)

Table 10. MS1133 Packaging Land Pattern Dimensions

Dimensions	Length
L	0.75
W	0.55
E	1.7
F	1

Packaging Information

Figure 22 shows the MS1183 packaging drawing




Figure 22. MS1183 Packaging Drawing (2.0X1.6 mm)

Table 11. MS1183 Packaging Dimensions

Dimensions	Min	Nom	Max
A	1.6 BSC		
B	2.0 BSC		
C	1.246	1.346	1.446
L	0.45	0.5	0.55
W	0.30	0.35	0.40
D	0.75 BSC		
E	0.95 BSC		
Package Edge Tolerance	0.1		
Mold Flatness	0.1		
Coplanarity	0.08		

Note: All dimensions are in millimeters

Packaging Land Pattern

Figure 22 shows the MS1183 PCB land pattern.
Note: All dimensions are in millimeters




Figure 23. MS1183 Packaging Land Pattern Drawing (2.0X1.6 mm)

Table 12. MS1183 Packaging Land Pattern Dimensions

Dimensions	Length
L	0.80
W	0.524
E	1.564
F	1.15

Note: All dimensions are in millimeters

Device Top Marking




Figure 24. MS1133 Device Top Marking Showing Pin 1

Table 13. MS1133 Device Marking Legend

Line	Position	Description
1	1	Product Marking
2	1-5	Lot Number
	6-7	Wafer Number
3	Lot Trace Code	
	1	Pin 1 Orientation Mark (Dot)
	2-3	Year (last two digits of the year)
	4-5	Calendar Work Week Number (1-53)
	7-8	Assembly Code

Device Top Marking




Figure 25. MS1183 Device Top Marking Showing Pin 1

Table 14. MS1183 Device Marking Legend

Line	Position	Description
1	1	Product Marking
2	1	Pin 1 Orientation Mark (Dot)
	2-5	Lot Number
	6	Wafer Number

Reflow Profile (IPC/JEDEC-STD-020)

Figure 26 shows the reflow profile for MS1133/MS1183




Figure 26. MS1133/MS1183 Reflow Profile

IMPORTANT NOTICE AND DISCLAIMER

MIXED-SIGNAL DEVICES INC. PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

Mailing Address: Mixed-Signal Devices Inc, 2 Venture, Suite 300, Irvine, California 92618, USA Copyright © 2026.